


SPECIFICATIONS

FRONT POLARIZER : TRANSMISSIVE,ADHESIVE
 BACK POLARIZER : TRANSMISSIVE,ADHESIVE
 DISPLAY MODE : TN, POSITIVE MODE
 DRIVE CONDITION : 1/4 DUTY, 1/3 BIAS, 5.0 V
 OPERATING TEMP : 0°C TO +50°C
 STORAGE TEMP : -10°C TO +60°C
 VIEWING DIRECTION : 6 O'CLOCK
 CUSTOMER P/N :
 CONNECTOR: PIN

一般误差要求
 除特别注明外, 其它尺寸误差要求:
 1) Linear 直线 $\pm 0.10\text{mm}$
 2) Angular 角度 $\leq \pm 1.0^\circ$

注: 未标注的尺寸按图纸实际测量尺寸。


SCALE: N.T.S.		SHEET: 1 OF 4	
GENERAL TOL. 0.20 MM	UNITS MM		
APPROVALS	DATE		
APP			
CHK			
DWN	06/09	DO NOT SCALE THIS DRAWING.	PROJECTION
		DRAWING NO: 73620G	
		DATE:	




LCD显示效果图
LCD DISPLAY EFFECT

一般误差要求
除特别注明外，其它尺寸误差要求：
1) Linear 直线 $\pm 0.10\text{mm}$
2) Angular 角度 $\leq \pm 1.0^\circ$

SCALE: N.T.S.			
SHEET: 3 OF 4			
GENERAL TOL. 0.20 MM	UNITS MM		
APPROVALS	DATE		
APP			
CHK			
DWN	06/09	DO NOT SCALE THIS DRAWING.	PROJECTION
		DRAWING NO: 73620G	
		DATE:	



COMMON



SEGMENT

PIN	1	2	3	4	5	6	7	8	9	10	11	12
COM1				COM1	1F	1A	2F	2A	3F	3A	4F	4A
COM2			COM2		1G	1B	2G	2B	3G	3B	4G	4B
COM3		COM3			1E	1C	2E	2C	3E	3C	4E	4C
COM4	COM4				1D	2D	COL	3D		4D	S1	

一般误差要求
除特别注明外，其它尺寸误差要求：
1) Linear 直线 $\pm 0.10\text{mm}$
2) Angular 角度 $\leq \pm 1.0^\circ$

SCALE:
N.T.S.

SHEET: 4 OF 4

GENERAL TOL.
0.20 MM

UNITS
MM

APPROVALS

DATE

APP

CHK

DWN

06/09

DO NOT SCALE THIS DRAWING.



PROJECTION

DRAWING NO:

73620G

DATE: